





- Will Drive 10 x 350 ohm or 20 x 700 ohm Load Cells
- Alibi Memory Stores 130,000+ Transactions
- 60,000 Displayed Divisions Performance
- · Counting Resolution 1.2 million
- Full Numeric & Functions Keyboard
- Tri-Color Display
- Multiple Data Collection
- Management Capabilities
- Real Time clock
- 100 PLU's

















PSCII Indicator

A Higher Level of Precision . . . A Higher Level of Performance

Model	PSCII Indicator
Divisions	Up to 60,000
Weighing Units	lb, kg
Functions	Counting, Statistics, Accumulation, Data Management
Tare Range	To capacity by subtraction
Power Source	Built-in rechargeable battery or external power adapter (included)
Display	Tri-Color backlit LCD Display
Connectivity	RS 232 Male & Female interfaces, 25 Pin relay port, External input port
Operating Environment	-10 to 40 ° C, non-condensing, R.H. ≤ 85%
Construction	ABS
Dimensions (W x D x H)	13 x 15 x 9
Net Weight	6 lbs.
Shipping Weight	7.5 lbs.
Options	Ticket Printer, Label printer

Features

Supports Single, Dual Range & Dual Interval operations

All Current Operation Results Output in Database Format for Data Management, Processing & Analysis

100 x PLU's per Each Platform (P1, P2 & P1+P2 Together)

Configurable Keypad, Check & System Buzzer

Real Time Clock

Alibi Memory to Store 130,000 Plus Transactions

Counting Resolution / Platform- 1.2 Million

Manual, Preset, Repetitive & Continuous Tare Operation

Continuous Tare with Configurable Delay Time Before Tare Action

Full Numeric & Functions Keyboard

Multi Search Criteria for Report Generation

Selectable Portrait / Landscape Ticket Printout Format

Customer & Product Code & Description Support Numbers, Alphabets & Selected Symbols

User Programmable and 10 x built-in Predefined Continuous / Interval Output Protocol

Check Result Control for Accumulation, Data Printout & Data Output

SupportsProductExpiryDurationInput&Output

Machine ID, Machine Group & Operator Number

Daily, Monthly, Specific Period Report Output

Supports Customer & Product Code & Description Input

Supports Inquiry, Setting & Execution Commands from a PC

10 x Quick PLU's for Unit Weight, Quantity Check Limits, Weight Check Limits, Pre-Set Tare, Customer & Product Code Description

Options

Secondary Weighing Platform Input

Wireless Connection Wifi, Blue tooth, 2.0/4.0 BLE

Stainless Steel U Shaped Bracket