RoughDeck® BDP Stainless Steel Barrel, Drum, Pallet Scale - Portable Model

Specifications

End Load Capacity:

1,000 lb: 100% full scale 2,500 lb: 80% full scale

Cable Length:

10 ft (3 m)

Threaded Eyebolt:

Hole (1/2-13 NC) located in center of deck for easy lifting

Warranty:

RoughDeck BDP weldment three years, load cells two years, all other components one year

Approvals:

NTEP CC 03-060, Class III 2,500 d Measurement Canada AM-5578 (500 kg) Class III 2,500 d (1,000 kg) Class III 2,000 d

Standard Features

- · Live siderails
- Top access foot adjustment holes
- Holes are 1/2-13 threaded for lifting scale
- Four adjustable stainless steel SUREFOOT™ support feet
- TuffSeal® JB4SS stainless steel, NEMA Type 4X junction box with signal trim card
- · Smooth top plate
- · IP66 stainless steel, welded-seal load cells

Dimensions with portability frame and hinged access ramps							
30 in x 31 in models							
Α	30.0 in (762 mm)	I	49.25in (1250.9 mm)				
В	31.0 in (787.4 mm)	J	52.25in (1327.1 mm)				
D	3.66 in (92.9 mm)	L	40.37 in (1025.4 mm)				
G	29.25 in (742.9 mm)	M	12.0 in (304.8 mm)				
Н	3.25 in (82.5 mm)						
36 in x 37 in models							
Α	36.0 in (914.4 mm)	I	55.25 in (1403.4 mm)				
В	37.0 in (939.8 mm)	J	58.25in (1479.5 mm)				
D	3.66 in (92.9 mm)	L	40.37 in (1025.4 mm)				
G	35.25 in (895.3 mm)	M	12.0 in (304.8 mm)				
Н	3.25 in (82.5 mm)						
Diet	Diatance from floor to top of contar weighing curface:						

Distance from floor to top of center weighing surface: 1.94 in (49.2 mm)

Distance from floor to bottom of weighing surface: 0.62 in (15.7 mm)



Part Number/Price

Part #	Size (W x L) Not Including Siderails	Capacity (Canadian Approved Capacities)	Est. Weight	Price				
77967	30 in x 31 in	1,000 lb (500 kg)	205 lb	Consult				
77968	30 in x 31 in	2,500 lb (1,000 kg)	205 lb	Consult				
77969	36 in x 37 in	1,000 lb (500 kg)	265 lb	Consult				
77970	36 in x 37 in	2,500 lb (1,000 kg)	265 lb	Consult				
Portability	Kits							
	le: Frame, two swivel and two fixed zir indicator stand	nc plated steel NSF approv	red wheels (75 lb	max. load				
78023	For use with 30 in x 31 in scale		90 lb	Consult				
78024	For use with 36 in x 37 in scale		100 lb	Consult				
RoughDec	k BDP Portability Kit, with conductive	wheels for use with 882IS						
199100	30 in x 31 in		25 lb	Consult				
199101	36 in x 37 in		30 lb	Consult				
Hinged ac	cess ramps: For use with portability ki	t						
78017	29.25 in x 12 in (sold individually)		25 lb	Consult				
78018	35.25 in x 12 in (sold individually)		30 lb	Consult				

Options/Accessories

Part #	Description	Price
Consult	Stainless steel deck with RL32218S-HE hermetically sealed IP69K stainless steel (cFMus approved) load cells and hardware	Consult
Consult	Stainless steel diamond treadplate safety deck	Consult

