

Summit® 3000

Low-profile Floor Scale



Specifications

End Load Capacity:

100% full scale at 2,000 lb and 5,000 lb
80% full scale at 10,000 lb

Cable Length:

20 ft (6.1 m) for connecting junction box to indicator

Warranty:

Summit 3000 weldment and load cells two years, all other components one year

Approvals:

NTEP CC 92-001A9, Class III 5,000 d
Measurement Canada AM-5530, Class III 5,000 d
(2,500 kg, 5,000 kg) 2,000 d (1,000 kg)

Standard Features

- Four NTEP Certified alloy steel shear-beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2-20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable. The load cell cable exits weldment toward the interior of scale, allowing flexibility to route out any side of scale to digital weight indicator.

APPROVALS



Measurement
Canada
Approved



Part Number/Price

Part #	Size (W x L x H)	Capacity	Est. Weight	Price
Single Scale				
74715	3 ft x 3 ft x 3.625 in	2,000 lb	190 lb	Consult
74716	4 ft x 4 ft x 3.625 in	2,000 lb	305 lb	Consult
74717	4 ft x 4 ft x 3.625 in	5,000 lb	305 lb	Consult
74718	4 ft x 4 ft x 3.625 in	10,000 lb	305 lb	Consult
74719	4 ft x 5 ft x 3.625 in	5,000 lb	395 lb	Consult
74720	4 ft x 5 ft x 3.625 in	10,000 lb	445 lb	Consult
74721	4 ft x 6 ft x 3.625 in	5,000 lb	470 lb	Consult
74722	4 ft x 6 ft x 3.625 in	10,000 lb	525 lb	Consult
74723	5 ft x 5 ft x 3.625 in	5,000 lb	505 lb	Consult
74724	5 ft x 5 ft x 3.625 in	10,000 lb	575 lb	Consult
Single Scale—Measurement Canada Approved				
77440	3 ft x 3 ft x 3.625 in	1,000 kg	190 lb	Consult
77373	4 ft x 4 ft x 3.625 in	1,000 kg	305 lb	Consult
77346	4 ft x 4 ft x 3.625 in	2,500 kg	305 lb	Consult
77347	4 ft x 4 ft x 3.625 in	5,000 kg	305 lb	Consult
82880	4 ft x 5 ft x 3.625 in	2,500 kg	395 lb	Consult
82881	4 ft x 5 ft x 3.625 in	5,000 kg	445 lb	Consult
77348	5 ft x 5 ft x 3.625 in	2,500 kg	505 lb	Consult
77349	5 ft x 5 ft x 3.625 in	5,000 kg	575 lb	Consult
Five-Scale Package				
75809	3 ft x 3 ft x 3.625 in	2,000 lb	850 lb	Consult
75810	4 ft x 4 ft x 3.625 in	2,000 lb	1,400 lb	Consult
75811	4 ft x 4 ft x 3.625 in	5,000 lb	1,400 lb	Consult
75812	4 ft x 4 ft x 3.625 in	10,000 lb	1,400 lb	Consult
75813	4 ft x 5 ft x 3.625 in	5,000 lb	1,870 lb	Consult
75814	4 ft x 5 ft x 3.625 in	10,000 lb	2,115 lb	Consult
75815	4 ft x 6 ft x 3.625 in	5,000 lb	2,210 lb	Consult
75816	4 ft x 6 ft x 3.625 in	10,000 lb	2,495 lb	Consult
75817	5 ft x 5 ft x 3.625 in	5,000 lb	2,325 lb	Consult
75818	5 ft x 5 ft x 3.625 in	10,000 lb	2,675 lb	Consult
Five-Scale—Measurement Canada Approved				
77472	3 ft x 3 ft x 3.625 in	1,000 kg	850 lb	Consult
77473	4 ft x 4 ft x 3.625 in	1,000 kg	1,400 lb	Consult
77474	4 ft x 4 ft x 3.625 in	2,500 kg	1,400 lb	Consult
77475	4 ft x 4 ft x 3.625 in	5,000 kg	1,400 lb	Consult
82885	4 ft x 5 ft x 3.625 in	2,500 kg	1,870 lb	Consult
82886	4 ft x 5 ft x 3.625 in	5,000 kg	2,115 lb	Consult
77476	5 ft x 5 ft x 3.625 in	2,500 kg	2,325 lb	Consult
77477	5 ft x 5 ft x 3.625 in	5,000 kg	2,675 lb	Consult

Options/Accessories

Part #	Description	Price
75819	Floor anchor plates, mild steel (set of two)	Consult
Consult	Top access foot adjust holes	Consult

*For custom sizes or capacities, please consult factory for RoughDeck® HP pricing