

Specifications

Internal Resolution:

1/500,000

Weight Display Resolution:

1/7,500 (1/6,000)

Display:

Liquid crystal display (LCD) with backlight

Weight: five-digit

Unit weight: five-digit

Quantity: six-digit

Power Source:

120 VAC power supply (U.S. power cord)

Number of Scale Channels:

One local scale

Memory Items:

25

Optional Battery:

Charge time: 12-14 hours

Estimated runtime: 300 hours (no backlight)

Operating Temperature:

14° F to 104° F (-10° C to 40° C)

Dimensions:

Overall (W x L x H): 335.7 x 349.7 x 123.5 mm (13 x 13 x 5 in)

Estimated Shipping Weight:

11 lb (5 kg)

Platter Size:

300 x 225 mm (12 x 8.9 in)

Warranty:

Two-year limited warranty



Standard Features

- Liquid crystal display (LCD) with yellow backlight
- 10 preset keys for product ID
- 25 item memory
- Internal resolution of 1/500,000
- Buzzer - low, ok, high

Part Number/Price

Part #	Description	Capacity	Est. Weight	Price
108248	DC-782	6 lb x 0.001 lb	11 lb (5 kg)	Consult
108249	DC-782	15 lb x 0.002 lb	11 lb (5 kg)	Consult
108250	DC-782	30 lb x 0.005 lb	11 lb (5 kg)	Consult
108251	DC-782	60 lb x 0.01 lb	11 lb (5 kg)	Consult

Options/Accessories

Part #	Description	Price
108516	Rechargeable battery	Consult
73382	AC adapter 110 VAC	Consult
108518	AC adapter 110 - 230 VAC (prior to May 2011 production units)	Consult
109429	Manual	Consult
73296	Carrying case	Consult